

HNR-400A MFR Digital Display Melt Flow Indexer



Which products to test



Glass fiber plastic



Polypropylene



Polycarbonate



Polyethylene



Nylon



Teflon



PVC



ABS

Application

This series high-precision melt flow rate instrument tester, used for testing all kinds of plastic, resin in the state of viscous flow through a certain temperature and load, every 10 min module and melt flow rate through the standard port MFR value, it is suitable for high temperature of polycarbonate, aromatic sulfone, fluorine plastics, nylon engineering plastics, can also be applied to polyethylene (PE), polystyrene (PS), polypropylene (PP), ABS resin, polyformaldehyde (POM), polycarbonate (PC) resin with lower melting temperature, such as plastic test, widely used in plastic production, plastic products, petrochemical industry and related colleges and universities.

Standards:

GB/T3682-2000 "Determination of Thermoplastic Melt Flow Rate and Melt Volume Flow Rate"

ISO 1133: 1997 "Determination of Thermoplastic Melt Mass Flow Rate MFR and Melt Volume Flow Rate MVR"

ASTM D1238 "Standard Test Method for Measuring Thermoplastic Melt Flow Rate by Extrusion Plastometer"

Specifications

Model	HNR-400A
Measuring Range	0.1-400.00g/10min (MFR)
Test method	Quality Act (MFR)
Temperature range	Room temperature—450℃
Temperature accuracy	±0.2℃
Temperature resolution	0.1℃
Timing range	1~9999s or 0.01-99.99s
Timing Accuracy	0.1 seconds
Material cutting method	manual way of cutting material
Display	LCD screen
Print	Equipped with a printer, can print test report
Squeeze out some material	
Discharge port diameter	Φ2.095±0.005mm
Discharge port length	8.000±0.025mm
Loaded barrel diameter	Φ9.550±0.025mm
Loaded barrel length	152±0.1mm
Piston head diameter	9.475±0.015mm

Piston head length	6.350±0.100mm
Standard test load (eight grades)	
1grade	0.325kg=(rod + weight + thermal units +1 No. tray body weight)
2grade	1.200 kg=(0.325+2 0.875 eight)
3grade	2.160 kg=(0.325+3 1.835 eight)
4grade	3.800 kg=(0.325+4 3.475 weight)
5grade	5.000 kg=(0.325+5 4.675 weight)
6grade	10.000kg=(0.325+5 4.675 weight+6 5.000 weight)
7grade	12.500kg=(0.325+5 4.675 weight+6 5.000+7 2.500 weight)
8grade	21.600 kg=(0.325+2 0.875+3 1.835+4 3.475+5 4.675+6 5.000+7 2.500+8 2.915 weight)
	Relative error of Load Test≤0.5%
Working conditions	Ambient temperature10℃—40℃; Relative humidity30%—80%
Power Supply	AC220V, 50Hz
Dimensions	250×350×510(L × W × H)
Weight	60KG



01

Various standard interfaces

Standard interface settings, safe use of electricity with confidence

02

Mini printer

With micro printer, print out test results





03


Automatic temperature control system

Double temperature control system, temperature control is more precise, heating efficiency is higher

Data Memory Function

The last test condition can be displayed on the boot, no need set again.







MACHINERY DIRECTIVE ATTESTATION OF CONFORMITY

Technical file of the company mentioned below has been inspected and audit has been completed successfully.

2006/42/EC Machinery Directive Annex VIII has been taken as references for these processes.

Company Name : **JINAN HENSGRAND INSTRUMENT CO., LTD.**

Company Address : NO.4915, WEST JINGSHI ROAD, JINAN, CHINA

Related Directives and Annex : **2006/42/EC Machinery Directive/Annex VIII**

Related Standards : **EN ISO 12100:2010, EN 60204-1:2018**

Product Name : **TESTING MACHINE**

Report No and Date : TCF-JHIC230128-MD

Product Brand/Model/Type : WDS-1, WDS-2, WDS-3, WDS-5, WDS-10, WDS-20, WDS-30, WDS-50, WDS-100, WDS-200, WDS-300, WDS-500, WDW-1, WDW-2, WDW-3, WDW-5, WDW-10, WDW-20, WDW-30, WDW-50, WDW-100, WDW-200, WDW-300, WDW-500, WDW-600, WDW-1000, WE-300, WE-600, WE-1000, WE-2000, WEW-300, WEW-600, WEW-1000, WEW-2000, WAW-300, WAW-600, WAW-1000, WAW-2000, WAW-3000, WAW-5000, WAW-6000, LAW-1000, JB-300B, JBS-300, JBW-300, JB-500B, JBS-500, JBW-500, JBW-750, CST-50, VU-2Y, VU-1S, DWC-40, DWC-60, DWC-80, DWC-100, DWC-196, YES-2000, YES-300, YAW-1000, YAW-300, YAW-2000, YAW-3000, YAW-5000, NDS-200, NDS-500, NDS-1000, NDS-2000, NDW-200, NDW-500, NDW-1000, NDW-2000, NDW-3000, NDW-5000, NDW-10000, HEZ-3, HEZ-6, HEZ-10, JWJ-10, TLS, TLW, HST-P50, HST-P100, HST-P200, HST-P300, RDJ, NDT, DWTT, GBW-60, GW-50, HST, XNR-400

Certificate Number : **M.2023.206.C81366**

Initial Assessment Date : 31.01.2023

Registration Date : 01.02.2023

Reissue Date/No : -

Expiry Date : **31.01.2028**

UDEM International Certification
Auditing Training Centre Industry
and Trade Inc. Co.

The validity of the certificate can be checked through www.udem.com.tr. Upon completion of EC declaration of conformity, it is used solely at the manufacturer's responsibility. This certificate remains the property of UDEM International Certification Auditing Training Centre Industry and Trade Inc. Co. to whom it must be returned upon request. The above named firm must keep a copy of this certificate for 15 years from the registration of certificate. This certificate only covers the product(s) stated above and UDEM must be noticed in case of any changes on the product(s)

Address: Mutlukent Mahallesi 2073 Sokak (Eski 93 Sokak) No:10 Çankaya - Ankara - TURKEY

Phone: +90 0312 443 03 90 **Fax:** +90 0312 443 03 76

E-mail: info@udem.com.tr www.udem.com.tr

